ANDREW FOSS

VESSEL SHEET

Official # 650273 ABS # 8209224

IMO # 8127543

Hull # 438





| VESSEL BESCRIPTION | | |
|--------------------|-------------------------------------|--|
| VESSEL DESCRIPTION | | |
| SERVICES | Harbor Ship Assist | |
| | Harbor Vessel Escort | |
| | | |
| CLASS NOTATIONS | ABS Load Line | |
| | Built to A1 Towing Vessel | |
| | Built to AMS | |
| | | |
| HAILING PORT | Seattle, WA | |
| CALL SIGN | WRB5166 | |
| KEEL LAID | | |
| DELIVERY | September 30, 1982 | |
| REBUILT | | |
| BUILDER | Tacoma Boat Building, Tacoma, WA | |

| MACHINERY | |
|----------------|---|
| CONFIGURATION | Voith Tractor |
| MAIN ENGINE | (2) EMD 16-645-E6 |
| REDUCTION GEAR | Voith AD 45-FH |
| PROPELLER | (2) 5 Bladed Voith Cycloidal Propellers |
| DRIVES/NOZZLES | |
| TOTAL RATED HP | 4,000 BHP @ 900 RPM |
| BOLLARD PULL | 46.13 ST (41.84 MT) Ahead |
| MAIN GENSET | (2) Detroit Diesel 6-71 Genset |
| AUX GENSET | |
| FIRE PUMP | 100 & 900 GPM |

| DIMENSIONS | |
|----------------|--------|
| REG. GT. | 298 |
| REG. NT. | 203 |
| ITC GT. | 372 |
| ITC NT. | 111 |
| DRAFT MIN | 11.8' |
| DRAFT MAX | 17' |
| REG. LENGTH | 106.7' |
| REG. BREADTH | 38.2' |
| MOULDED DEPTH | 14'-3" |
| LENGTH OVERALL | 106.7' |
| BEAM OVERALL | 38'-3" |
| AIR DRAFT | 50'-6" |
| DISPLACEMENT | 683 LT |

| REGULATORY | |
|------------|---|
| ABS LL | Υ |
| ABS CLASS | N |
| USCG INSP | Υ |
| REGISTRY | Υ |
| COASTWISE | Υ |
| SOLAS | N |

| CREWING REQ. | |
|------------------|--|
| DOM. < 600 NM | |
| INTL OR > 600 NM | |
| MAX. BERTHS | |

| TANK CAPACITIES | |
|-----------------|------------|
| FUEL CAPACITY | 50,550 gal |
| FUEL TYPE | MGO |
| UREA | N/A |
| HYDRAULIC | 2,100 gal |
| WASTE OIL | |
| BALLAST | |
| HOLDING TANKS | |
| LUBE OIL | 2,400 gal |
| POTABLE WATER | 5,400 gal |
| NON-POTABLE | |

| DECK GEAR | |
|--------------------------------|---|
| ANCHOR GEAR | 1,500 LBF, 540' of 1-1/8" Chain |
| BOW WINCH | Intercon HSW-40 W/ Stbd Capstan |
| BOW LINE | 150' of 5" Circ. Plasma |
| BOW LINE PULL & BRAKE CAPACITY | |
| TOW WINCH | Intercon SD-200 Single Drum |
| TOW LINE | (2) 305' of 8" Circ. Plasma 12x12, 7" Eye |
| TOW LINE PULL & BRAKE CAPACITY | Mid-Drum: 45,000 LBF @ 60 FT/MIN & 200,000 LBF Brake Capacity |